


K1527A Series

5V Surface Mount Voltage Controlled Crystal Oscillator




- **Applications:** Phase-Locked Loops (PLL's), Clock Recovery, Reference Signal Tracking, Synthesizers, Frequency Modulation, Modem, Modulo
- 2.0 to 33.1 & 51.84 MHz Frequency Range
- Dual Polarity Control Voltage
- 0.5V to 5.0V Control Voltage
- ±20 ppm Stability (Typical)
- Variety of Deviation Sensitivity Options
- -40°C to +85°C Operating Temperature Available

OBSOLETE



*K1527AC (Height) = 7.49mm Max

ELECTRICAL SPECIFICATIONS		
Model	K1527AA	K1527AC
Frequency Range (MHz)	2 to 33	51.840
Input Current (6A)	< 26	< 50
Frequency Control Function	(For Custom Deviation Range, Vc Range, etc. – Consult Factory)	
Deviation (ppm)		
Minimum	±130	±115
Maximum	±200	±175
Deviation Sensitivity (ppm/V)	26 to 40	23 to 35
Linearity (%)	< 5	< 15
Modulation Bandwidth (+3dB)	> 30KHz	> 20 KHz
Nominal Control Voltage (V)	2.5	
Control Voltage Range (V)	-5.0 to +5.0	
Transfer Function	Positive	
Input Impedance	> 50KΩ @ 10KHz	
Frequency Stability (ppm)		
Overall	Inclusive of Calibration, Temperature, Voltage, Load, and Aging	
0°C to +70°C	±45	±20
-40°C to +85°C	+60	+35
Temperature Range (°C)		
Operating	-40°C to +85°C	
Storage	-40°C to +125°C	
Supply Voltage (V)	+5.0V ±5%	
Symmetry (%) TTL	45/55	
Symmetry (%) CMOS	<33MHz 45/55; >33MHz 40/60	
Start Up Time (ms)	< 10	
Typical SSB Phase Noise (dBC/Hz)	10Hz	-65
Offset from Carrier	100Hz	-95
	1KHz	-120
	10KHz	-140
	100KHz	-150




MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.


K1527A Series

5V Surface Mount Voltage Controlled Crystal Oscillator




PIN	FUNCTION
1	Voltage control
7	Gnd & Case Plane
8	Output
14	+V _{cc}

SHIPPING TUBE CROSS SECTION




ALL DIMENSIONS ARE INSIDE

OUTPUT WAVEFORM



TEST CIRCUIT DIAGRAM



MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS

TEST METHODS	REFERENCE PROCEDURES	DESCRIPTION
Temperature Cycle	MIL-STD-833, Mtd 1010, Cond. B	-55°C to +125°C; Air-to-Air, 100 cycles; 10 min. dwell
Mechanical Shock	MIL-STD-883, Mtd 2002, Cond. B	1500 g's
Vibration	MIL-STD-883, Mtd 2007, Cond. B	20-2000 Hz; 0.06 inch; 15g's; 3 planes
Humidity Steady State	MIL-STD-202, Mtd 103	40°C; 90%-95% R.H.; 56 days
Thermal Shock	MIL-STD-883, Mtd 1011.7, Cond. B	100°C to 0°C; Water-to-Water; 15 cycles
Electrostatic Discharge	MIL-STD-883, Mtd 3015 Class II	2 KV to 4 KV Threshold
Solderability	MIL-STD-883, Mtd 2022.2	Solder dip; Meniscograph Criteria
Hermeticity	MIL-STD-883, Mtd 1014.8, Cond. A1	Mass spectro. 2 x 10 ⁻⁸ atmos. CC/sec He
Resistance to Soldering	MIL-STD-202, Mtd 210D, Cond. C	260°C; 10 seconds; 1 inch/sec.
Lead Integrity	MIL-STD-883, Mtd 2004.5, Cond. A, B1	Lead tension & bend stress
Marking Permanence	MIL-STD-883, Mtd 2015.8	Resistance to solvents
Life Test	MIL-STD-883, Mtd 1005.6	125°C, powered, 1000 hours minimum

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.