

OBSOLETE




M4001 & M4002 Series 9x14 mm, 5.0 or 3.3 Volt, Sinewave, VCSO




Ordering Information		M4001/M4002	1	3	V	S	K	-R	00.0000
Product Series									
M4001 = 3.3 V									
M4002 = 5.0 V									
Temperature Range									
1: 0°C to +70°C									
7: 0°C to +85°C									
Stability									
3: ±100 ppm (typical)									
Output Type									
V: Voltage Controlled									
Symmetry/Output Type									
S: 45/55% Sinewave									
Package/Lead Configurations									
J: J-lead									
K: FR-4									
RoHS Compliance									
Blank: non-RoHS compliant part									
-R: RoHS compliant part									
Frequency (customer specified)									

- Low Jitter - <1 ps from 12 kHz to 20 MHz
- Ideal for clock smoothing application for OC-48 and OC-192


J-Lead Package



FR-4 Package



SUGGESTED SOLDER PAD LAYOUT



Pin Connections

PIN	FUNCTION
1	Control Voltage
2	Ground
3	RF Out
4	+Vdd

PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition/Notes
Frequency Range	F	622.08		2488	MHz	See Note 1
Operating Temperature	T _A	(See Ordering Information)				
Storage Temperature	T _s	-55		+125	°C	
Frequency Stability	ΔF/F	(See Ordering Information)				
Aging						
1st Year						
Thereafter (per year)						
Pullability/APR		50			ppm	See Note 2
Control Voltage	V _c	0		3.3	V	M4001
		0		5.0	V	M4002
Linearity				15	%	Positive Monotonic Slope
Modulation Bandwidth	f _m	500			kHz	-3dB Bandwidth
Input Impedance	Z _{in}	50k			Ohms	
Input Voltage	V _{dd}	3.135	3.3	3.465	V	M4001
		4.5	5.0	5.5	V	M4002
Input Current	I _{dd}		50	80	mA	M4001
			70	100	mA	M4002
Output Type						Sinewave
Load			50		Ohms	See Note 3
Symmetry (Duty Cycle)		45/55		55/45	%	@ 0 VDC
Output Power	P _o	+2	+5	+8	dBm	M4001
		+4	+7	+10	dBm	M4002
Start up Time						
Sub-Harmonic Levels				-20	dBc	
Non-Harmonic Levels				-60	dBc	
Phase Jitter	φ _J					
@ 1244.16 MHz			0.10	0.3	ps RMS	Integrated 12 kHz - 20 MHz
Phase Noise (Typical)	10 Hz	100 Hz	1 kHz	10 kHz	100 kHz	Offset from carrier
@ 1244.16 MHz	-35	-63	-90	-117	-152	dBc/Hz

1. Consult factory for extended temperature operation and exact frequency availability.
2. APR specification inclusive of initial calibration, deviation over temperature, shock, vibration, supply voltage, and aging.
3. See load circuit diagram #3.


MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.

OBSOLETE



MtronPTI Lead Free Solder Profile



MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.