

SX2050 Surface Mount Crystals




***SX2050-R 00.0000 MHz** (customer specified)

-R signifies RoHS compliant part

M1011Sxxx - Contact factory for datasheet

Equivalent Series Resistance (ESR), Max.	Sx2050
Fundamental (AT-cut)	
3.579 to 3.999 MHz	200 Ω
4.000 to 4.499 MHz	150 Ω
4.500 to 4.999 MHz	120 Ω
5.000 to 6.999 MHz	100 Ω
7.000 to 8.999 MHz	80 Ω
9.000 to 9.999 MHz	60 Ω
10.000 to 12.999 MHz	50 Ω
13.000 to 18.999 MHz	35 Ω
19.999 to 30.000 MHz	25 Ω
Fundamental (BT-cut)	
30.000 to 40.000 MHz	30 Ω
Third Overtones (AT-cut)	
36.000 to 60.000 MHz	80 Ω



	PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition/Notes	
Electrical Specification	Frequency Range	F	3.579545		60	MHz		
	Frequency Tolerance	F/F			±50	ppm		
	Frequency Stability	ΔF/F			±100	ppm	See Note 1	
	Operating Temperature	T _A	-20		+70	°C		
	Storage Temperature	T _S	-55		+125	°C		
	Aging 1 st Year					+3	ppm	Up to 3 rd year
	Thereafter (per year)					+5	ppm	
	Load Capacitance	C _L			18		pF	See Note 2
	Shunt Capacitance	C ₀			5		pF	
	ESR			See ESR Table				
	Drive Level	D _L	25	50	100		μW	
	Insulation Resistance	I _R	500				MΩ	
Environmental	Mechanical Shock	MIL-STD-202, Method 213, C (100 g's)						
	Vibration	MIL-STD-202, Method 201 & 204 (10 g's from 10-2000 Hz)						
	Thermal Cycle	MIL-STD-883, Method 1010, B (-55°C to 125°C, 15 min dwell, 10 cycles)						
	Hermeticity	MIL-STD-202, Method 112 (must meet 1 x 10 ⁻⁸)						
	Solderability	Per EIAJ-STD-002						
Max Soldering Conditions	See solder profile, Figure 1							

Note 1: BT Cut fundamentals from 24.000 to 40.000 MHz have a stability of ±100 ppm

Note 2: Series resonant designated by "SR" prefix (ie., SRSX2050)


MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.

OBSOLETE



MtronPTI Lead Free Solder Profile



MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.