

M6055 & M6056 Series

2.5 x 3.2 mm, 3.0 V, Clipped Sine Wave, TCXO/VCTCXO

Features:

- Ultra Miniature Package
- Tight Stability Performance
 - Down to ± 0.5 ppm
- Standard 4 Pad Configuration

Applications:

- Telecommunications such as SONET / SDH / DWDM / FEC / SERDES / OC-3 thru OC-192
- Wireless base stations / WLAN / Gigabit Ethernet
- Avionic flight controls and military communications


Ordering Information

	M6055	1	J	S	N	00.0000 MHz
Product Series	M6055 = TCXO M6056 = VCTCXO					
Temperature Range	1: 0 °C to +70 °C H: -30 °C to +85 °C 2: -40 °C to +85 °C					
Stability	H: ± 2.5 ppm J: ± 1.0 ppm G: ± 0.5 ppm					
Output Waveform	S: Clipped Sine Wave					
Package/Lead Configurations	N: 4 Pad Leadless Ceramic					
Frequency (customer specified)						

M6055Sxxx & M6056Sxxx - Custom datasheets.



All dimensions in inches [mm].



Pin Connections

Pin	Function
1	N/C or Control Voltage
2	Ground/Case
3	Output
4	+V _{DD}

Parameter	Symbol	Min	Typ	Max	Units	Conditions
Frequency Range	F _R	10.0		52.0	MHz	
Frequency Tolerance	$\Delta F/F$	-1.0		+1.0	ppm	@ +25 °C, initial
		-1.5		+1.5	ppm	@ +25 °C, after two reflow soldering profiles
Frequency Stability	$\Delta F_T/F$	(See Ordering Information)			ppm	Over Operating Temperature
Frequency vs Supply Voltage	$\Delta F_{VDD}/F$	-0.2		+0.2	ppm	For $\pm 10\%$ voltage change
Frequency vs Load	$\Delta F_{LOAD}/F$	-0.2		+0.2	ppm	For $\pm 10\%$ load change
Aging		-1.0		+1.0	ppm	per year @ +40 °C
Operating Temperature	(See Ordering Information)					
Input Voltage	V _{DD}	2.85	3	3.15	V	
Input Current	I _{DD}			2	mA	
Output Type	Clipped Sine Wave					
Output Load	10 k Ω 10 pF					
Output Level		0.8			V _{pk-pk}	
Control Voltage	V _{CT}	0.5	1.5	2.5	V	M6056 only.
Frequency Tuning		± 5		± 12	ppm	M6056 only. V _{CT} = +1.5 V
Phase Noise (Typical)			-85		dBc/Hz	@ 10 Hz
			-110		dBc/Hz	@ 100 Hz
			-135		dBc/Hz	@ 1 kHz
			-150		dBc/Hz	@ 10 kHz
Environmental	Mechanical Shock	Per MIL-STD-202, Method 213 (2000 g, 0.3 ms duration, 1/2 sine wave)				
	Vibration	Per MIL-STD-202, Method 201 & 204 (10 g from 20 Hz to 2000 Hz)				
	Hermeticity	Per MIL-STD-202, Method 112 (1x10 ⁻⁸ atm.cc/s of helium) (Crystal unit only)				
	Storage Temperature	-55 °C to +105 °C				
	Solderability	Per EIAJ-STD-002				
	Max Soldering Conditions	See Solder Profile, Figure 1				
Package	4-pad 2.5 X 3.2 X 1.0 mm leadless ceramic. RoHS compliant.					

MtronPTI Lead Free Solder Profile

