

SPECIFICATION FOR HC-49U/S-SMD CRYSTAL MtronPTI P/N M1001S483


Electrical Specifications:

Parameter	Symbol	Min.	Typ.	Max.	Units	Conditions
Mode of Oscillation		Fundamental (AT-Cut)				
Frequency	F ₀		4.194304		MHz	
Frequency Tolerance	F/F	-30		+30	ppm	@ +25°C
Frequency Stability	ΔF/F	-50		+50	ppm	
Operating Temperature	T _A	-10		+70	°C	
Aging		-5		+5	ppm	First year @ +25°C
Load Capacitance	C _L		12		pF	
Shunt Capacitance	C ₀			7	pF	
ESR				80	Ω	
Drive Level	D _L	25	100	500	μW	

Environmental & Mechanical Requirements:

Mechanical Shock	Per MIL-STD-202, Method 213, Condition C.
Vibration	Per MIL-STD-202, Methods 201 & 204
Thermal Cycle	Per MIL-STD-883, Method 1010, Condition B
Storage Temperature	-55°C to +125°C
Hermeticity	Per MIL-STD-202, Method 112 (1 x 10 ⁻⁸ atm cc/s of Helium)
Solderability	Per EIAJ-STD-002
Max. Soldering Conditions	See Figure 1
Package Type	2-pad HC-49U/S-SMD resistance weld. RoHS compliant.

Figure 1






SPECIFICATION FOR HC-49U/S-SMD CRYSTAL
MtronPTI P/N M1001S483

Dimensions, Marking, and Pin Out Information:

Part Marking	
Line 1	MFFFFVXY
Line 2	M1001S483

Legend	
M	MtronPTI
F	Frequency
V	Vendor code
X	Month
Y	Year



DATA SHEET REVISION TABLE:

Date	Rev.	Author	Details of Revision
6/2/11	0	WNJ	Original release.
6/17/11	A	WNJ	Changed Max. ESR from 30 Ω to 80 Ω .