

## SPECIFICATION FOR RoHS 6 COMPLIANT HCMOS SMT OSCILLATOR MtronPTI P/N M2002T234

### Electrical Specifications:

Parameter	Symbol	Min.	Typ.	Max.	Units	Conditions
Frequency of Operation	F <sub>o</sub>		100.000000		MHz	
<b>Frequency Stability</b>						
vs. Temperature	ΔF/F	-25		+25	ppm	Includes initial accuracy @ +25°C and deviation over operating temperature range.
vs. Aging		-3		+3	ppm	1 <sup>st</sup> year
		-2		+2		Thereafter (per year)
<b>RF Output</b>						
Output Type		HCMOS/TTL Compatible				
Output Load				15/2	pF/TTL	
Symmetry (duty cycle)	T <sub>DC</sub>	45	50	55	%	Ref to ½ V <sub>DD</sub>
Logic "1" Level	V <sub>OH</sub>	90% V <sub>DD</sub>			V	HCMOS load
		V <sub>DD</sub> - 0.5				TTL Load
Logic "0" Level	V <sub>OL</sub>			10% V <sub>DD</sub>	V	HCMOS load
				0.5		TTL Load
Rise/Fall Time	T <sub>R</sub> /T <sub>F</sub>			2	nS	10% to 90% V <sub>DD</sub> HCMOS load 0.5 V to 2.4 V TTL load
Tristate Logic		80% V <sub>DD</sub> or N/C			V	Pad 1: Output Enabled
				20% V <sub>DD</sub>	V	Pad 1: Output Disabled to high-Z
Start-Up Time				10	mS	
<b>Supply Voltage &amp; Power Consumption</b>						
Operating Voltage	V <sub>DD</sub>	3.0	3.3	3.6	V	
Operating Current	I <sub>DD</sub>			50	mA	
<b>Additional Specifications</b>						
Random Jitter	R <sub>J</sub>			10	pS RMS	1-Sigma

### Environmental & Mechanical Requirements:

Operating Temperature	T <sub>A</sub>	-40		+85	°C	
Storage Temperature	T <sub>S</sub>	-55		+125	°C	
Mechanical Shock	Per MIL-STD-202, Method 213, Condition C (100 g's, 6 mS duration, ½ sinewave)					
Vibration	Per MIL-STD-202, Method 201 & 204 (10 g's from 10-2000 Hz)					
Thermal Cycle	Per MIL-STD-883, Method 1010, Condition B (-55°C to +125°C, 15 min. dwell, 10 cycles)					
Hermeticity	Per MIL-STD-202, Method 112, (1x10 <sup>-8</sup> atm. cc/s of Helium)					
Solderability	Per EIAJ-STD-002 Environmental					
Max. Soldering Conditions	See solder profile, Figure 1					
Package Type	5.0 x 7.0 x 1.4 mm, 4-pad Ceramic Leadless Chip Carrier (M2 type)					

## SPECIFICATION FOR RoHS 6 COMPLIANT HCMOS SMT OSCILLATOR MtronPTI P/N M2002T234

### Dimensions, Marking, and Pin Out Information:

Pad	Function
1	Tristate
2	Ground
3	Output
4	+V <sub>DD</sub>

Part Marking	
Line 1	M2002T234
Line 2	100M0000
Line 3	M yy ww vv

Legend	
yy	Year
ww	Work week
vv	Factory code





Figure 1

### Datasheet Revision Table:

Date	Rev.	Author	Details of Revision
05/27/14	0	MM	Original release.
7/23/14	A	MM	Updated rise/fall and current.